

Twin Housing Lightweight, Portable Handcart Filter Pumps

Remove Water, Dirt, and Other Contaminants from Oils and Fuels
MCP5E, Two-Stage Series-Flow Model
MDP5E, One-Stage Alternate-Flow Model

FEATURES

- 5 gpm Standard, 1 and 10 gpm Optional
- Economical two-cartridge configurations
- Choice of different cartridge combinations
- Quick and easy cartridge change
- Minimum fluid spill during operation
- Self-contained, one person operation

DESCRIPTION

MCP5E Series-Flow – This model employs two different types of filter cartridges in series. Typically, the first of the MCP's two housings is utilized as a prefilter. With heavy carbon or dirt contamination, this prefilter holds a cost-effective particle or colloidal removal cartridge and the second in series holds an **Aquacon**[®] super-absorbent water removing cartridge.

Other cartridge combinations have proven to be effective for filtering vacuum pump oil and other oils in corrosive environments. Use either an economical dirt cartridge or an **Aquacon**[®] dirt and water cartridge in the first stage and either a Fuller's Earth or an Activated Alumina cartridge in the second. The first stage removes dirt or dirt and water while the second removes acids, gums, surfactants, varnishes, soaps, color bodies, corrosive gasses, polar compounds, and oxidation products.

MDP5E Alternate-Flow – Only one housing on this model is utilized at a time. The operator can manually switch the oil flow from one housing to the other at his option. This is very useful when down-time is critical. The oil can filter through one side while the cartridge is being changed in the other housing with little or no interruption of oil flow.

Another application of the MDP5E is to use a different type of cartridge in each of the housings. An economical dirt removing cartridge, for example, can be employed in the first housing for routine filtering. When water is detected in the oil, the flow can be manually diverted to the second housing, containing an **Aquacon**[®] Cartridge, for both water and dirt removal.



MDP5E-1

Contact your local Velcon Representative regarding other types of cartridges and cartridge combinations which are available.

APPLICATIONS

Hydraulic Oil
 Gear Oil
 Lube Oil
 Transformer Oil
 Vacuum Pump Oils:
 Hydrocarbon Base
 Perfluoropolyethers

Heat Transfer Fluids
 Cutting Oil
 Mineral Oil
 Phosphate Ester Oils
 Synthetic Oils
 Diesel Fuel
 Biodiesel

SPECIFICATIONS

Standard Features, MCP5E and MDP5E

- 5 gpm standard flow rate
- Epoxy powder coated vessel, both interior and exterior
- Band Clamp vessel closure – no tools required
- Operating pressure to 100 psi
- 10" semi-pneumatic wheels
- Self-priming positive displacement pump with built-in pressure relief valve
- Static Pressure Gauge on each housing – to indicate when cartridge must be changed
- 1/2 hp, 115V, 1-phase, 60 Hz, 10 Amp TEFC Motor
- 10 ft. 3-wire power cord
- 10 ft. Inlet and Discharge Hose, 3/4" I.D.
- 3/4" NPT Male Fittings on hose ends
- Suction Y-Strainer mounted at pump inlet
- Weight: 157 lbs.
- Shipping Weight: 202 lbs.
- Height: 52", Width: 22", Depth: 22"

ORDERING INFORMATION

Specify model number as shown below.

MCP5E-1 or MDP5E-1 115 v, 1-ph, 60 Hz

MCP5E-2 or MDP5E-2 230 v, 1-ph, 60 Hz

(Note: Units are shipped without filter cartridges.)

Also available: 1 gpm units, 10 gpm units, 3-phase power, 50 Hz power, explosion proof motor, air motor (contact Velcon for more information)

OPTIONS & ACCESSORIES

550Y020 Flow Control Bypass

552Y030 Filter Bypass

553Y035 Four-way Valve

554Y001 Sample Tap

703Z004 Differential Pressure Gauge (MCP)

703Y004 Differential Pressure Gauges (MDP)

722Y006 Digital Flowmeter

725Y009 High Pressure Shut-off Switch

RECOMMENDED SPARES

Filter Cartridge, box of 6 ea

G-1016 Std Buna-N Filter Housing Lid Gasket, 2 ea

G-1016A Viton-A Filter Housing Lid Gasket, 2 ea

FILTER CARTRIDGE SELECTION:

Application	Cartridge	Filter Area, Sq. In.	Micrometer Rating, Specify:	Notes
Dirt Removal: Particulates	FO-718PL Series Pleated Media	5000	1/3, 1/2, 1, 2, 5, 15, or 50	Maximum particle filtration
Dirt Removal: Colloidals	FO-618FGA Series Depth Media	N/A	5, 10, or 25	Most cost effective for "slime" removal
Dirt and Water Removal	AC/AD-718 Series Aquacon [®]	2500	1 or 5	Removes dirt and 1 to 2 quarts water
		2900	1/2	For circuit breaker & high-carbon oils
Acid Removal	LA-71801B Fuller's Earth			Use 1 gpm Filter Pumps
	LB-71801 Activated Alumina			Use 1 gpm Filter Pumps



Velcon products are sold and serviced by a world-wide representative network. To order, contact Headquarters or your **LOCAL REPRESENTATIVE:**

COMPANY HEADQUARTERS:

Velcon Filters, LLC
1210 Garden of the Gods Road
Colorado Springs, CO 80907-3410
Phone: 1.800.531.0180 / 1.719.531.5855
Fax: 719.531.5690
e-mail: vfsales@velcon.com
www.velcon.com

MANUFACTURING PLANTS LOCATED AT:

Colorado Springs, Colorado
Sylacauga, Alabama
Henryetta, Oklahoma

OFFICES & AFFILIATES IN:

Canada, Germany, Singapore & Spain



**Liquid Filtration
and Separation
Specialists**